

novalite




for home/office/hotel lighting

9W Dimmable Downlight



ITEM	NL-DL-9W-WW/CW
CRI	>82
LED Chip	Samsung 5630
Beam Angle	90°
Voltage	AC200~240V 50/60Hz
Operating Temp.	-10~45°C
Life Span	>40,000h
Replacement	Traditional lamps
Dimming	Clipsal Trailing edge, universal, leading edge dimmer.

Installation Instruction



Unit: mm



Cut Out:
90~100mm

1-Tools to open the appropriate holes in the ceiling.

2-Connect the AC power.

power driver


Spring clasp



3- (A) Place spring clasp in an upward position.

(B) Place in hole

DRIVER



4-Release spring clasp and push into place.



Product benefits :

- 1-Controllable via smart devices.
- 2-Easy to install and use
- 3-Contains no mercury

Areas of application :

- 1-General indoor illumination
- 2-Hospitality

Product features :

- 1-Color rendering index Ra: >82
- 2-Dimmable
- 3-life span > 40,000h
- 4-color temperature : 2700k-3000k
- 5-LED Chip : SAMSUNG 5630
- 6-Beam Angle : 90

Power

9W

Lumen

650lm

700lm

750lm

CCT

Warm White

Neutral White

Cool White

Finish

White

Silver